



**HAL**  
open science

## Probabilistic Coalition Structure Generation

Nicolas Schwind, Tenda Okimoto, Katsumi Inoue, Katsutoshi Hirayama,  
Jean-Marie Lagniez, Pierre Marquis

► **To cite this version:**

Nicolas Schwind, Tenda Okimoto, Katsumi Inoue, Katsutoshi Hirayama, Jean-Marie Lagniez, et al.. Probabilistic Coalition Structure Generation. 16th International Conference on Principles of Knowledge Representation and Reasoning (KR'18), 2018, Tempe, Arizona, United States. pp.663-664. hal-03300777

**HAL Id: hal-03300777**

**<https://univ-artois.hal.science/hal-03300777v1>**

Submitted on 20 Jun 2022

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Probabilistic Coalition Structure Generation

**Nicolas Schwind**

National Institute of Advanced  
Industrial Science and Technology  
Tokyo, Japan  
email: nicolas-schwind@aist.go.jp

**Tenda Okimoto**

Faculty of Maritime Sciences  
Kobe University  
Kobe, Japan  
email: tenda@maritime.kobe-u.ac.jp

**Katsumi Inoue**

National Institute of Informatics  
Tokyo Institute of Technology  
Tokyo, Japan  
email: inoue@nii.ac.jp

**Katsutoshi Hirayama**

Faculty of Maritime Sciences  
Kobe University  
Kobe, Japan  
email: hirayama@maritime.kobe-u.ac.jp

**Jean-Marie Lagniez<sup>1</sup> and Pierre Marquis<sup>1,2</sup>**

<sup>1</sup>CRIL-CNRS, Université d'Artois,  
<sup>2</sup>Institut Universitaire de France  
Lens, France  
email: {lagniez,marquis}@cril.fr

## Abstract

We introduce a model for probabilistic coalition structure generation (PCSG). This model generalizes the standard CSG model to the case when some of the agents considered at start may be finally defective but a new coalition structure based on the remaining agents cannot be formed. In a PCSG, one seeks to maximize the expected utility of a coalition structure. Two policies making precise how the value of a coalition structure evolves when some agents are missing are also introduced.

$F(CS) = \sum_{C_i \in CS} f(C_i)$ . A coalition structure  $CS \in \Pi_A$  is *optimal* if for each  $CS' \in \Pi_A$ ,  $F(CS') \leq F(CS)$ .

**Example 1** Let  $\langle A, f \rangle$  be a CSG with  $A = \{a_1, a_2, a_3\}$  and  $f$  be defined as  $f(\{a_1\}) = 30$ ,  $f(\{a_2\}) = 40$ ,  $f(\{a_3\}) = 0$ ,  $f(\{a_1, a_2\}) = 90$ ,  $f(\{a_1, a_3\}) = 120$ ,  $f(\{a_2, a_3\}) = 100$ , and  $f(\{a_1, a_2, a_3\}) = 150$ . Among all five coalitions structures,  $CS_1 = \{\{a_1, a_3\}, \{a_2\}\}$  is an optimal one, with  $F(CS_1) = f(\{a_1, a_3\}) + f(\{a_2\}) = 120 + 40 = 160$  (The results for all coalitions structures are reported in Table 1.)

## Setting and Motivation

Coalition Structure Generation (CSG) (Rahwan et al. 2015) considers a finite set of agents where every subset, or *coalition*, is associated with a value (through a *characteristic function*) which represents some pay-off associated with the underlying performance of the coalition. The goal is to find a partition of agents, or *coalition structure*, so that the sum of coalition values is maximized.

In CSG, it is assumed that when forming a coalition structure, what is foreseen is what is got: the agents are supposed to be fully reliable and the pay-off associated with each coalition is obtained as expected. However, in realistic settings, this cannot be reasonably expected to hold. Some unexpected events may occur, e.g., agents getting sick or being unable to do the job for various reasons. So we might be uncertain about the actual capabilities or even the attendance of each agent. The *probabilistic CSG* (PCSG) setting we introduce next precisely aims to model such situations.

## Preliminaries on CSG

**Definition 1 (CSG)** A CSG is a pair  $\langle A, f \rangle$  where  $A = \{a_1, \dots, a_n\}$  is a set of agents and  $f : 2^A \rightarrow \mathbb{R}^+$  is a characteristic function. A coalition is a non-empty subset of  $A$ . A coalition structure  $CS$  is a partition of  $A$ .  $\Pi_A$  denotes the set of all coalition structures (over  $A$ ).

$f(C)$  is called the *value* of a coalition  $C \subseteq A$ , and  $F(CS)$  is the value of a coalition structure  $CS \in \Pi_A$  defined as

Copyright © 2018, Association for the Advancement of Artificial Intelligence (www.aaai.org). All rights reserved.

## Probabilistic CSG

In our probabilistic CSG (PCSG) setting, an agent may not fulfil its role as initially expected, i.e., may be “lacking” from the coalition it is assigned to. We assume that such events may only occur after a coalition structure is formed, and recomputing a coalition structure based on the remaining agents is not an option (this happens, for instance, when the agents from different coalitions committed themselves to work on different projects.) Then one must define how the value of a coalition is updated after the occurrence of an event. In addition, the uncertainty of each event will be represented by a probability value. Doing so, we will be able to associate each coalition structure with an *expected utility*.

More formally, a probabilistic CSG (PCSG) extends the standard CSG setting as follows. Let  $A$  be a finite set of agents. Given  $P \subseteq A$ , we denote  $\bar{P} = A \setminus P$ . Given  $P \subseteq A$ , an *outcome*  $\omega_P$  is a situation where each agent from  $P$  (resp.  $\bar{P}$ ) is in the state “present” (resp. “absent”) after being assigned to a coalition.  $\Omega_A$  denotes the set of all outcomes. We define  $\mathcal{E}_A = \{\langle Q, R \rangle \mid Q, R \subseteq A, Q \cap R = \emptyset\}$ , where each  $\langle Q, R \rangle$  is an *event* defined as  $\langle Q, R \rangle = \{\omega_P \in \Omega_A \mid Q \subseteq P, P \cap R = \emptyset\}$ . Let  $p : \Omega_A \mapsto [0, 1]$  be a probability distribution (i.e.,  $\sum_{P \subseteq A} p(\omega_P) = 1$ ). One extends the domain of  $p$  to events from  $\mathcal{E}_A$  as  $p(\langle Q, R \rangle) = \sum_{\omega_P \in \langle Q, R \rangle} p(\omega_P)$  for each  $\langle Q, R \rangle \in \mathcal{E}_A$ . Thus  $p(\langle Q, R \rangle)$  denotes the probability of the event  $\langle Q, R \rangle$  to occur. Lastly, the characteristic function in a PCSG, denoted now  $g$ , maps each coalition  $C \subseteq A$  and each event  $\langle Q, R \rangle \in \mathcal{E}_A$  to a value. In other words, the value of the coalition  $C$  is made precise in the context of the event  $\langle Q, R \rangle$ .

$\Pi_A$	CSG	caut.	flex.
$CS_1 = \{\{a_1, a_3\}, \{a_2\}\}$	<b>160</b>	49.6	71.2
$CS_2 = \{\{a_1, a_2\}, \{a_3\}\}$	90	<b>72</b>	80
$CS_3 = \{\{a_1, a_2, a_3\}\}$	150	12	<b>86</b>
$CS_4 = \{\{a_2, a_3\}, \{a_1\}\}$	130	34	66.4
$CS_5 = \{\{a_1\}, \{a_2\}, \{a_3\}\}$	70	64	64

Table 1: Example: the list of all coalition structures from  $\Pi_A$ , and for each  $CS_i \in \Pi_A$ , the value  $F(CS_i)$  and the expected utility of  $U(CS_i)$  in both the cautious and flexible PCSG settings, for each coalition structure  $CS_i \in \Pi_A$ .

Formally, a PCSG is defined as follows:

**Definition 2 (PCSG)** A PCSG is a tuple  $\langle A, g, p \rangle$  where  $A = \{a_1, \dots, a_n\}$  is a set of agents;  $p : \Omega_A \rightarrow [0, 1]$  is a probability distribution; and  $g : 2^A \times \mathcal{E}_A \rightarrow \mathbb{R}^+$  is a characteristic function such that for each coalition  $C$  and each event  $\langle Q, R \rangle \in \mathcal{E}_A$ ,  $g(C, \langle Q, R \rangle) = g(C, \langle Q \cap C, R \cap C \rangle)$ .

The condition on  $g$  above requires the value of a coalition to be affected only by outcomes that involves a change in it. This assumption is consistent with that made in the standard CSG framework, where the value of a coalition  $C_i \in CS$  does not depend on the value of the other coalitions  $C_j \in CS$ ,  $j \neq i$ . The value of a coalition structure  $CS$  is defined for each event  $\langle Q, R \rangle \in \mathcal{E}_A$  as  $G(CS, \langle Q, R \rangle) = \sum_{C \in CS} g(C, \langle Q, R \rangle)$ . Then one seeks to maximize the *expected utility* of a coalition structure  $CS$ , defined as  $U(CS) = \sum_{\omega_P \in \Omega_A} p(\omega_P) \cdot G(CS, \langle P, \bar{P} \rangle)$ .

Interestingly, given a coalition structure  $CS \in \Pi_A$ , the computation of  $U(CS)$  can be characterized in a coalition-wise fashion; i.e., for each  $C \in CS$ , one computes an “expected utility”  $u(C)$  that does not depend on the events involving agents from  $\bar{C}$ :

**Proposition 1** Given a PCSG  $\langle A, g, p \rangle$ , for each coalition structure  $CS \subseteq \Pi_A$ , we have that  $U(CS) = \sum_{C \in CS} u(C)$ , where  $u(C) = \sum_{Q \subseteq C} p(\langle Q, C \setminus Q \rangle) \cdot g(C, \langle Q, C \setminus Q \rangle)$ .

There is a number of ways  $g$  can be defined. In a CSG, each coalition  $C$  produces a reward  $f(C)$  corresponding to some implicit “task” to be performed by  $C$ . When some agents are missing from  $C$ , i.e., in an outcome  $\omega_P \in \Omega_A$  such that  $\bar{P} \cap C \neq \emptyset$ , different situations may arise depending on the context. One may allow each residual coalition  $C' = C \cap P$  to be *flexible*, so that it can be freely reassigned to another task and produce the corresponding reward. This assumption is reasonable when one considers, for instance, a set of wireless sensors in a network whose goal is to optimize some global connectivity in a utilitarian fashion.

**Definition 3 (Flexible PCSG)** A flexible PCSG is a PCSG  $\langle A, g_{fle}^f, p \rangle$ , where  $g_{fle}^f : 2^A \times \mathcal{E}_A \rightarrow \mathbb{R}^+$  is characterized by a function  $f : 2^A \rightarrow \mathbb{R}^+$  such that for each  $C \subseteq A$  and each  $\langle Q, R \rangle \in \mathcal{E}_A$ ,  $g_{fle}^f(C, \langle Q, R \rangle) = f(C \cap Q)$ .

In contrast, one could assume that no residual coalition can be reassigned to another task; then a more *cautious* behavior should be considered and no reward can be obtained from it, e.g., when the tasks need preparation ahead of time.

**Definition 4 (Cautious PCSG)** A cautious PCSG is a PCSG  $\langle A, g_{cau}^f, p \rangle$ , where  $g_{cau}^f : 2^A \times \mathcal{E}_A \rightarrow \mathbb{R}^+$  is characterized by a function  $f : 2^A \rightarrow \mathbb{R}^+$  such that for each  $C \subseteq A$  and each  $\langle Q, R \rangle \in \mathcal{E}_A$ ,  $g_{cau}^f(C, \langle Q, R \rangle) = f(C)$  if  $C \subseteq Q$ , otherwise  $g_{cau}^f(C, \langle Q, R \rangle) = 0$ .

**Example 1 (continued)** Assume that the attendance of any agent does not affect the one of other agents, i.e., the events  $\langle \{a_1\}, \emptyset \rangle$ ,  $\langle \{a_2\}, \emptyset \rangle$  and  $\langle \{a_3\}, \emptyset \rangle$  are independent, and that  $p(\langle \{a_1\}, \emptyset \rangle) = 0.8$  ( $a_1$  is lacking 20% of the time),  $p(\langle \{a_2\}, \emptyset \rangle) = 1$  ( $a_2$  is fully reliable), and  $p(\langle \{a_3\}, \emptyset \rangle) = 0.1$  ( $a_3$  is lacking almost every time).<sup>1</sup> Table 1 reports the expected utilities for both cautious and flexible PCSG settings.

If each task requires a solid preparation, the cautious PCSG setting should be used. Although  $CS_1$  is optimal in the standard CSG case, it is not the best choice in the cautious PCSG case. Indeed, as the probability of attendance of  $a_3$  is quite low, it is “risky” to assign  $a_3$  to a coalition with some other agents. Instead,  $CS_2$  is the best choice. Indeed, even if  $a_3$  put alone produces no reward, the other coalition  $\{a_1, a_2\}$  is formed of reliable agents and produces a relatively high value.

If now one considers possible to reassign the residual coalitions to another task, the flexible PCSG is to be used and  $CS_3$  is the best choice. Compared to  $CS_2$  (the best one in the cautious PCSG case), in  $CS_3$  the agent  $a_3$  is together with  $a_1$  and  $a_2$ . This is harmless since here, the absence of  $a_3$  does not result in a breakdown of the whole coalition.

## Perspectives

Our next step is to design encodings and algorithms for computing a coalition structure of maximal expected utility for both cautious and flexible PCSGs. Because the size of the characteristic function  $f$  would be in  $\mathcal{O}(2^n)$  when represented extensively as a table ( $n$  being the number of agents), we plan to focus on some of the existing succinct representation languages in CSGs such as Marginal Contribution networks (MC-nets) (Jeong and Shoham 2005). Doing so, we will be able to investigate how some existing encodings for solving MC-net based CSGs, such as the MILP encoding from (Ohta et al. 2009), can be adapted to PCSGs.

## Acknowledgments

This work was supported by JSPS KAKENHI Grant Number JP17H00763.

## References

- Jeong, S., and Shoham, Y. 2005. Marginal contribution nets: a compact representation scheme for coalitional games. In *EC’05*, 193–202.
- Ohta, N.; Conitzer, V.; Ichimura, R.; Sakurai, Y.; Iwasaki, A.; and Yokoo, M. 2009. Coalition structure generation utilizing compact characteristic function representations. In *CP’09*, 623–638.
- Rahwan, T.; Michalak, T. P.; Wooldridge, M.; and Jennings, N. R. 2015. Coalition structure generation: A survey. *Artificial Intelligence* 229:139 – 174.

<sup>1</sup>Note that  $p : \Omega_A \mapsto [0, 1]$  is fully characterized.